



## FEATURES

- Liquid cooled exhaust manifold
- Oil cooler
- Radiator and fan standard
- Centrifuge oil filter
- Oil cooled pistons
- Optional AFR controls
- Removable wet liners
- Power Units or Gensets

## Natural Gas Fueled Engine for Oil Well Pumping Services Power Units Gensets

- Natural Gas Oil wells
- Pumping services
- Prime power for facilities
- Hydraulics power
- Irrigation power
- Backup power
- Emergency power
- Compressor power

## APPLICATIONS

## SPECIFICATIONS

	DNG-8800 ENA	DNG-8800 ETA
<b>Configuration</b>	<b>6-cylinder (inline)</b>	
<b>Bore x Stroke</b>	<b>4.65 x 5.32 in</b>	
<b>Engine Displacement</b>	<b>537 cubic in</b>	
<b>Compression Ratio</b>	<b>9.0:1</b>	
<b>Complete Power Unit Dry Weight (With Radiator)</b>	<b>3170 lbs</b>	<b>3750 lbs</b>
<b>Firing Order</b>	<b>1-5-3-6-2-4</b>	
<b>Natural Gas Fuel Pressure Requirements</b>	<b>6-8 inches of H<sub>2</sub>O / 7.5 - 8 PSI Max</b>	
<b>Rotation</b>	<b>Counter clockwise (facing the flywheel)</b>	
<b>Aspiration</b>	<b>NA (Naturally Aspirated)</b>	<b>TA (Turbocharged Aftercooled)</b>
<b>Air Filter</b>	<b>Dry</b>	
<b>Battery Charging System</b>	<b>12 V 63 Amp</b>	
<b>Rated Power Max Output with fan at 1800 rpm</b>	<b>128 BHP</b>	<b>170 BHP</b>
<b>Continuous Power Rating with fan at 1800 rpm</b>	<b>115 BHP</b>	<b>158 BHP</b>
<b>Governor Type</b>	<b>Electronic 65 mm throttle body</b>	
<b>Flywheel Housing Size</b>	<b>SAE 1</b>	
<b>Oil change Capacity with Filters</b>	<b>22 quarts</b>	
<b>Coolant Capacity with Radiator</b>	<b>13,5 gallons / 50/50 coolant mix</b>	
<b>Clutch - 3 inch shaft O,D,</b>	<b>Single disc SAE 1 - Twin disc type</b>	

## ENGINE RATINGS

